

HSK – Ihr Partner für Kunststoffschweiß- und Biegetechnik
HSK – Your partner for plastic welding – and bending technology

Hand welding extruder HSK26 GSX DATA



BASIC EXTRUDER

- Extrusion welding from PEHD, PP, PVC* and PVDF
 - temperature probe, location in the melt chamber
 - Control units for actual / desired mass and air temperature and actual speed
 - Digital recording of the welding temperature, ambient temperature, the speed and the welding times on SD Card
 - Various welder programmed with its own SD card
 - Pre-programmable welding and building materials on SD card
 - Evaluated logs and charts on Excel
 - Cold start protection
 - 1 pce nozzle blank included
 - Speed control
- *PVC with special screw

TECHNICAL DATA

Output	2.5 kg/h (with PEHD pellets)
Heating extruder	700 W / air 2.200 W
Drive	1.150 W
Air requirement	300 l/min.
Voltage	230 V / 50Hz
Weight	8.5 kg
Guarantee	screw and cylinder 24 months

HSK26 GFX DATA (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 2.300 W

ADDITIONAL EQUIPMENT

- | | | |
|----------------------|----------------------------|---------------|
| ▪ Welding nozzles | Extruder nozzle preheating | Angle adaptor |
| ▪ Transportation box | Prolongation | Air compactor |
| ▪ Widen | | |

Technical execution subject to modifications