

HSK – Ihr Partner für Kunststoffschweiß- und Biegetechnik  
HSK – Your partner for plastic welding – and bending technology

## Hand welding extruder HSK40 RFX /HSK40 RSX



### BASIC EXTRUDER

- Extrusion welding from PEHD, PP, PVDF and PVC\*
  - temperature probe, location in the melt chamber
  - rod feeding, no additional gearing
  - Control units for actual / desired mass and air temperature
  - Cold start protection
  - Rod diameter 3,4 and 5 mm
  - 1 pce nozzle blank included
- \*PVC with special screw

### TECHNICAL DATA

Output	3.8 kg/h (with PEHD rod 5 mm)
Heating extruder	700 W / air 2200 W
Drive	1.100 W
Air requirement	300 l/min.
Voltage	230 V / 50Hz
Weight	8 kg
Guarantee	screw and cylinder 24 months

### HSK40 RSX (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 2200 W

### ADDITIONAL EQUIPMENT

- |                      |                            |               |
|----------------------|----------------------------|---------------|
| ▪ Welding nozzles    | Extruder nozzle preheating | Angle adaptor |
| ▪ Transportation box | Prolongation               | Air compactor |
| ▪ Welding rod        | Widen                      |               |

Technical execution subject to modifications